

# SPESSORE RACCORDI IN PE80-100

fittings wall thickness PE80-PE100  
 épaisseur des raccords PE80-PE100  
 espesor de los racords PE80-PE100

## PE 80-MRS8-SIGMA63

DN	DE	SDR41 PN3,2	SDR33 PN4	SDR26 PN5	SDR17 PN8/S8	SDR11 PN12,5/S5	SDR7,4 PN20
15	20	-	-	-	1.6	2.0	2.8
20	25	-	-	-	1.6	2.3	3.5
25	32	-	-	-	2.0	3.0	4.5
32	40	-	-	2.0	2.3	3.7	5.6
40	50	-	-	2.2	2.9	4.6	6.9
50	63	-	2.0	2.5	3.6	5.8	8.7
65	75	2.0	2.4	2.9	4.3	6.9	10.4
80	90	2.2	2.8	3.5	5.1	8.2	12.5
100	110	2.7	3.5	4.3	6.3	10.0	15.2
100	125	3.1	3.9	4.9	7.1	11.4	17.3
125	140	3.5	4.4	5.4	8.0	12.8	19.4
150	160	3.9	5.0	6.2	9.1	14.6	22.1
150	180	4.4	5.6	7.0	10.2	16.4	24.9
200	200	4.9	6.2	7.7	11.4	18.2	27.6
200	225	5.5	7.0	8.7	12.8	20.5	31.1
250	250	6.1	7.8	9.7	14.2	22.8	34.5
280	280	6.9	8.7	10.8	15.9	25.5	38.7
300	315	7.7	9.8	12.2	17.9	28.7	43.5
350	355	8.7	11.1	13.7	20.1	32.3	49.0
400	400	9.8	12.4	15.4	22.7	36.4	55.2
500	450	11.0	14.0	17.4	25.5	41.0	62.1
500	500	12.2	15.5	19.3	28.3	45.5	-
560	560	13.7	17.4	21.6	31.7	51.0	-
600	630	15.4	19.6	24.3	35.7	57.3	-
700	710	17.4	22.1	27.4	40.2	-	-
800	800	19.6	24.9	30.8	45.3	-	-
900	900	22.0	28.0	34.7	51.0	-	-
1000	1000	24.4	31.0	38.5	56.6	-	-
1100	1100	26.9	34.2	42.4	62.5	-	-
1200	1200	39.3	37.2	6.2	-	-	-

## PE 100-MRS10-SIGMA80

DE	SDR41 PN4	SDR26 PN6,3	SDR17 PN10/S8	SDR11 PN16/S5	SDR9 PN20	SDR7,4 PN25	SDR6 PN32
20	-	-	-	2.0	2.3	3.0	3.4
25	-	-	-	2.3	3.0	3.5	4.2
32	-	-	2.0	3.0	3.6	4.4	5.4
40	-	-	2.4	3.7	4.5	5.5	6.7
50	-	2.0	3.0	4.6	5.6	6.9	8.3
63	-	2.5	3.8	5.8	7.1	8.6	10.5
75	-	2.9	4.5	6.8	8.4	10.3	12.5
90	2.2	3.5	5.4	8.2	10.1	12.3	15.0
110	2.7	4.2	6.6	10.0	12.3	15.1	18.3
125	3.1	4.8	7.4	11.4	14.0	17.1	20.8
140	3.5	5.4	8.3	12.7	15.7	19.2	23.3
160	4.0	6.2	9.5	14.6	17.9	21.9	26.6
180	4.4	6.9	10.7	16.4	20.1	24.6	29.9
200	4.9	7.7	11.9	18.2	22.4	27.4	33.2
225	5.5	8.6	13.4	20.5	25.2	30.8	37.4
250	6.2	9.6	14.8	22.7	27.9	34.2	41.5
280	6.9	10.7	16.6	25.4	31.3	38.3	46.5
315	7.7	12.1	18.7	28.6	35.2	43.1	52.3
355	8.7	13.6	21.1	32.2	39.7	48.5	59.0
400	9.8	15.3	23.7	36.3	44.7	54.7	-
450	11.0	17.2	26.7	40.9	50.3	61.5	-
500	12.3	19.1	29.7	45.4	55.8	-	-
560	13.7	21.4	33.2	50.8	-	-	-
630	15.4	24.1	37.4	57.2	-	-	-
710	17.4	27.2	42.1	-	-	-	-
800	19.6	30.6	47.4	-	-	-	-
900	22.0	34.4	53.3	-	-	-	-
1000	24.5	38.2	59.3	-	-	-	-
1100	27	42.1	65.2	-	-	-	-
1200	29.4	45.9	-	-	-	-	-