

FLEX ible PE electrofusion bar

PE PIPE AXIAL RESTRAINT



Permanently attached to pipe by electrofusion the Plastitalia S.p.A. Flex is a flexible bar designed to restraint PE pipe axial movement:



Flex can be welded on PE pipe in order to obtain an anchoring system



Flex is used to avoid the pipe movement or to fix something along the pipe



Flex can be used for centering and easy sliding of a PE pipe in another pipe.

FLEX ible PE electrofusion bar


PE PIPE AXIAL RESTRAINT

Features

4 mm terminal pins

The special design of the product allows a simpler use of the ratchet strap



A unique design of the electrical system avoids the movement of wires and eliminates risk of smoke and spout of material



Technical Specifications:


- Fits any PE pipe in the size range of 160 - 1600 mm (or 6" - 63")
- Made of PE 100 (PE4710).
- Can be welded by any standard EF control box with barcode wand or manual input (25V).
- Axial broking force: 50 kN for single Flex.

L	H	B	Wt.
188 mm	40.5 mm	62 mm	250 gr
7.40 inch	1.59 inch	2.44 inch	0.55 inch



Easy Installation:

Hold one or multiple flex to the pipe by using ratchet strap.



Designed and tested to support 50 kN (5000 kg) of axial force.
Use multiple units to achieve required force.